



DESCRIPTION

The **Tecbor® Joint Paste** is a powder plaster made of calcium carbonate, resin and various additives. It has been specially formulated for **Tecbor®** panel joint treatment.

APPLICATION AND USAGE

Tecbor® Joint Paste can be used in conjunction with the joint tape. The mix ratio is 11 litres of water for each 25 kg sack.

Before treating the joints, all the gaps caused by flaking, chipping or merely by a faulty panel joint must be filled.

It can be applied by hand, using a taping knife and a trowel. It must be given a layer, be let to dry, apply the joint tape and then cover completely.

Temperature during application and drying must be between 5 °C and 30 °C. Do not apply to dirty or damp surfaces or surfaces at temperatures of less than 5 °C. Avoid application in strong winds.

Do not apply on substrates that are frozen or defrosting, nor on hot surfaces or in direct sunlight.

Do not add water or powder to the paste if it begins to set.

For upright salient angles, use reinforced tape.

TECHNICAL CHARACTERISTICS AND SPECIFICATION

Apperance	white powder
Tape adherence	> 1.000 g.
Cracking	no cracking up to 5-mm thick.
Raw density	700 kg/m³ (± 100 kg/m³)
Particule size	less than 200 µ
Type of setting	sets in contact with the environment.
Setting time	24 hours (it may vary depending on weather conditions)

PERFORMANCE AND PACKAGING

The performance for joints is about 350 g/cm².

It is available in 20 kg sacks on covered pallets

HYGIENE AND SAFETY

• Hygiene:

Tecbor® Joint Paste is not harmful in itself but it does contain some elements that are.

- **Industrial hygiene:** ensure it is handled in a ventilated area to reduce dust and vapour concentration.
- **Breathing protection:** it may cause slight irritation, coughing and chest pains when inhaled. If this happened, get some fresh air. No breathing protection whatsoever is needed under normal conditions of use provided the space is sufficiently ventilated.
- **Hand protection:** contact with skin is not considered to be particularly hazardous under normal conditions of use. Wash hands and any other parts of the body that may have been in contact with it with water and soap before eating, drinking, smoking, etc.
- **Eye protection:** it may cause reddening of the eyes if in contact; if so, immediately rinse your eyes with running water. It is advisable to carry adequate protection to meet the working conditions while handling the product.
- **Ingestion:** it is not considered to be particularly hazardous if ingested under normal conditions of use.

If the product is accidentally spilled on the floor, sweep and remove the product spilled from the relevant containers. Dilute the remainder and thin

Clean work tools with abundant water.

• Safety:

This is not a flammable product. All fire extinguishers may be used.

Tecbor® joint paste is not a hazardous product and does not require special labelling.

*We guarantee that the quality of our materials conforms to the indicated technical specifications, while it remains the consumer's own responsibility to determine how suitable the product is for the intended use. You must perform tests and ensure the effectiveness of the product for its application. **mercortecresa**® does not guarantee, explicitly or implicitly, the compatibility of a product for any particular application. We cannot be held responsible for any damage or accident resulting from the use of our products*

STORAGE

9 months in its original unopened packaging and kept in a cool dry place.

Store away from heat sources and/or frost.